



Product Enhancements and Model Code Updates

Release Date: 5/23/14

Products Affected: 2200/2220, 2023A, 2026, and 2027A Series Valves

For More Information: Applications Engineering 877-667-6413



Norriseal products have set industry standards for over 50 years. As we continue to improve our product and simplify our offering, we have made some updates to our 2200/2220, 2023A, 2026, and 2027A series valves that will help you simplify the selection of valves without giving up the options you require.

Norriseal will implement several hardware upgrades, which we anticipate will go mostly unnoticed, and we will begin to phase out some obsolete options. There will be a few changes affecting nomenclature that you may notice as we implement these improvements. The following upgrades and option changes will be made:

- All 303 SS, 316 SS, and 17-4PH SS stems will be replaced by NACE (MR0175) suitable Nitronic 50 stem material as a standard. Nitronic 50 is a strong and robust material, and is more corrosion resistant than 300 series stainless or 17-4PH.
- Standard Buna-N seals will be replaced with Low Temperature, Peroxide Cured Buna, with an expanded temperature range of -50°F to 180°F (from -20°F to 180°F). Since it is Peroxide Cured, it is suitable for both H₂S and CO₂ service. It will become our standard for NACE-compliant valves and Viton will continue to be available for higher temperature applications.
- 316 SST 2200/2220 valves will now be sold standard as NACE MR0175 (2002 version) compliant.
- 2023A will now be available with only two trim size configurations and will be NACE-compliant as a standard, without a travel indicator.
- 2029 Series has been discontinued.

Our most recent brochure reflecting these changes is available. Please don't hesitate to contact our sales, marketing, or customer service departments if you have any questions.

Notes

- TECHNICAL BULLETINS DO NOT ENHANCE OR EXTEND AN EXISTING WARRANTY, AND DO NOT INCLUDE OR CREATE ANY WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Preventive service repairs will generally not be performed under warranty during the normal warranty period if a product is not exhibiting the particular symptom or problem or if the problem would not otherwise be covered by a warranty. Technical Bulletins are not recalls.
- Any product alterations by anyone other than Norriseal will defeat the design of the product. Accordingly, Norriseal will not be liable for any problems caused by such alterations.
- Technical Bulletins are provided for informational purposes only. Complete detailed information is not provided in each bulletin. If a problem or symptom exists or suspected to exist, Norriseal should be consulted promptly.
- As we continue to receive questions and comments, this bulletin will be updated as necessary.
- Prior to any H₂S application, a complete evaluation of the products, applications and systems should be completed to confirm the design meets any and all applicable health and safety requirements. Norriseal assumes no liability for the application and system performance of any design.
- Due to the continuous improvement at Norriseal, specifications and/or prices are subject to change without notice or obligation.

Engineered Performance

Norriseal is an ISO 9001-certified manufacturer of level and pressure control products, level gauges, control valves, butterfly valves, check valves and regulators. For more than five decades, Norriseal products have set performance standards in oil and gas production, gas transmission, refining, chemical processing, marine, power generation and other industrial applications.



Tel: 713-466-3552
Fax: 713-896-7386
www.norriseal.com

©2014 Norriseal. All rights reserved.

[™]Norriseal is a mark of Dover Corporation. All other marks are property of their respective owners.